ProSoft®
T E C H N O L O G Y

DATASHEET

BACnet/IP™, EtherNet/IP™, Modbus TCP/IP®, and Modbus® RTU to LonWorks® QuickServer Gateways PS-QS-1x11-F

The QuickServer line of communication gateways are designed to link building automation networks utilizing LonWorks with industrial control networks communicating on BACnet/IP, EtherNet/IP, Modbus TCP/IP, and Modbus RTU. The QuickServer gateways are available with limits of up to 250 or 500 points of application data.

Specifications

Field Connections
- Ethernet 10/100 RJ45
- Serial RS-485 terminal (up to 115K baud)
- FTT-10 LonWorks port

Environment
- Operating temperature: -40°F to 167°F (-40°C to 75°C)
- Relative humidity: 5% to 90% RH, with no condensation

Power Requirements
- 9 to 30 Vdc or Vac or 5 Vdc
- Current draw 250mA @ 12V

Other
- Configuration/Diagnostic utilities
- Capacity: 250 or 500 Points
- Table, Wall or DIN rail mount

Physical Dimensions (W x D x H)
- 4.5 x 3.2 x 1.6 in. (11.5 x 8.3 x 4.1 cm)
- 0.4 lbs (0.2 Kg)

Approvals
- TUV approved to UL 916 standard
- CE Mark
- BTL Mark (PS-QS-1010)
- RoHS Compliant
- FCC Part 15 Compliant

Ordering Information

To order this product, please use the following:

PS-QS-1011-F   250 Points
PS-QS-1211-F   500 Points

How to Contact Us: Sales and Support

Sales and Technical Support for this product are provided by ProSoft Technology. Contact our worldwide Sales or Technical Support teams directly by phone or email:

Asia Pacific
+603.7724.2080, asiapc@prosoft-technology.com

Europe – Middle East – Africa
+33 (0) 5.34.36.87.20, Europe@prosoft-technology.com

North America
+1.661.716.5100, support@prosoft-technology.com

Latin America (Sales only)
+1.281.298.9109, latinam@prosoft-technology.com